

General Information:



Gewicht/ weight	2.2 kg
Einbaulage/ installation position	beliebig/ various
Betriebsdruck/ operating pressure (P)	min. 250 bar max. 420 bar
max.Druck/ max. pressure (T)	<20 bar
max. Volumenstrom/ max. recommended flow	80 l/min

Surface:

gal. beschichtet / electroplating coated

Hydraulic data:

Druckflüssigkeit/ Hydraulic medium	(HL, HLP) per ISO 6743-4 2015
Temperatur/ temperature range	-20 to +100 °C
Umgebungstemperatur/ environmental temperature	< +50 °C
Viskositätsbereich/ Viscosity range	2.8 - 500 mm²/s
Verschmutzungsgrad/ degree of contamination	ISO 4406 18/16/13



Ident-Nummer part number	Druckwert (bar) pressure value
416.001.403.9	420
4xx.xxx.xxx.9	NN
4xx.xxx.xxx.9	NN

Anschluss/ port	Anschlussgröße/ size	Norm	Anzugsmoment/ torque	Erläuterung/ annotation
P	SAE 1"	ISO 6162-2 (SAEJ 518 Code62)	see specification	Versorgungsleitung/ supply port
T1	G1/2"	ISO 1179-1	see specification	tank
Reinke	prepared on	22.06.22	project no.	part no. 416.001.403.9 index 00 page 1 of 2

